

RECOAT - GRAFFITI REMOVER

Article Number: 21837



— RECOAT —

PRODUCT DESCRIPTION

The Recoat Graffiti Remover is a spray especially for the easy removal of graffiti.

AREA OF APPLICATION

For removing Graffiti on Recoat Anti Graffiti systems .

JOB DESCRIPTION

Apply the remover or remover gel with a brush or cloth, allow 3 minutes to solve the graffiti, then remove the remover with the graffiti. We advise to remove Graffiti within one week. For older or heavier graffiti the treatment may have to be repeated.

First apply the remover gel, after 3 minutes remove the gel with a (paper) towel or cloth. Then give the area a final wipe with the standard remover on a cloth or a graffiti wipe. In this way no substance will be absorbed in the ground and the cleaning materials can be disposed of as chemical waste.



TECHNICAL PROPERTIES

Base	Clear waterborne coating on acrylate basis
Approximate specific density	0,97 KG/L
Colour	Colourless
VOC content	1054 g/L
Application by means of	Brush, Microfiber cloth, Spray
Application	Wear gloves and ensure sufficient ventilation
Transport	Temperature during storage, transport and application minimum 5° C and maximum 30°C at a relative humidity of Maximum 85%
Storage stability	Unopened a maximum of two years in case of dry cool and frost-free storage.

SELECTION AND PREPARATION OF THE SUBSTRATE

Depends on the condition of the substrate. No residue may remain after cleaning, rinsing is therefore very important. Any problems in most cases are the result of insufficient cleaning or the use of wrong materials. The Recoat warranty will cease to apply in all of these cases. The final result depends on the treatment and the condition of the substrate.

Recoat will not assume any responsibility for failures caused by insufficient cleaning or the use of wrong materials.

SAFETY

All Recoat products comply with the REACH standard. The user of this product must comply with health safety and health regulations environment. Safety data sheet can be found at www.recoat.eu

ENVIRONMENT

The product contains very small quantities of solvent and is largely manufactured in accordance with the green chemistry method.

IMPORTANT INFORMATION

Recoat products are for professional use only. Specified processing and drying times are highly dependent on the conditions under which the product is used. It is of great importance that the applicator has sufficient knowledge of the substrate to which a specific product is applied. His knowledge and expertise determine the final result. Therefore no rights can be derived from these guidelines.